

Technical data sheet

Chamber is built into transportable container with light and power utilities.
Decompression chamber is completely Germany TÜV Nord certified, ready for use.

Max. Operating pressure
Max. Working pressure
Test pressure

Main chamber capacity
Prechamber capacity

internal diameter
Inside length of the main chamber
Inside length of the pre chamber

Length over everything
Overall width
Overall height



5,5 bar
5,0 bar
7,87 bar

6 Personen sitzend
2 Personen liegend

2000 mm
4000 mm
1155 mm

ca. 5.155 mm
ca. 2020 mm
ca. 2050 mm

Mobile Hyperbaric Medical chamber in the 40 foot container with treatment room the doctor

Total volume

Main chamber with
BIBS Masks
Prechamber with
BIBS Masks

material
Number of doors
PC Round doors, Ø
MC Rectangular door

Number of windows in the
MC and PC
Diameter
Lateral control station
Diameter



17.800 l
6

2

P265GH
3
2 / 800 mm
1

3

200 mm
1
200 mm

NATO/STANAG/DIN 13256 -Bajonett- Flange on the prechamber

1

Electrical power
Electrical connection value
Acceptance company (classification)
Weight of the chamber including 16Stk Cylinders, installed in the 20 'standard container
40 Fuß High Cube 20' long and 9'6 "high outside dimensions

380 Volt, 50 Hz
ca. 4000 Watt
TÜV Nord
ca. 8.500 kg
Länge: 12.050 mm
Breite: 2438 mm
Höhe: 2891 mm